

TECHNICAL DATA SHEET

270052

Esfera Clear Topcoat 052 SMT

Indoor Transparent super matt Water-Based Topcoat

FEATURES						
Properties:	Good levelling	Silky touch	Good transparency	Good transparency		
Recommended use:	For all types of furniture	Woodwork	Doors and indoor w	Doors and indoor windows		
Application method:	Spray Gun	Airmix gun	Airless gun	Airless gun		
Recommended Hardeners:						
Recommended solvents:	Water					
AVAILABLE GLOSSES	<u> </u>		•			
270052	10 - 12 (60°)	270057	75 - 85 (60°)	75 - 85 (60°)		
270053	20 - 25 (60°)					
270054	32 - 38 (60°)					
270055	51 - 56 (60°)					
TYPICAL PROPERTIES (25 °C)	1	-	-			
Supply Viscosity, mPa.s	3000 - 4000					
VOC content (%w)	4.36					
GENERAL FEATURES	<u>'</u>		,			
Preparation		Tunnel dry				
Dust -free drying of 120 g/m ²	25 min	Flash off	25°C	10 min		
Touch-free drying of 120 g/m ²	1 h	Laminar flow Area	40 - 45°C	60 min		
Stackable	After 24 h	Cooling		10 min		
Recommended Quantity	100-140 μ					

SUBSTRATE PREPARATION

Apply over water based sealer 270051. It is necessary to sand the surface previously with 280-320 grit paper and make sure that the substrate is completely clean of dust, dry and free of any contaminant (silicone, grease, remains of varnish...)

APPLICATION ADVICE

We recommend to apply at 15 - 25 $^{\circ}$ C and 50 -75% relative humidity. If possible, use of a preheater t 30 - 35 $^{\circ}$ C is recomended Air renovation is necessary 3/4 times per hour in drying chambers.

Every tool used should be made of stainless steal. They should be clean immediatly with water or appropriate solvents

Application	% Thinner	Nozzles	Air Pressure (bar)	Pump Pressure (bar)
Spray Gun	5 - 10	2.5	3 - 4	
Airmix	0 - 7	11 - 13	0.5 - 1	80 -120
Airless	0 - 7	11 - 13		100 - 150

PRECAUTIONS

Mix properly before using.

Paint residues must be removed according to current regulations.

With regard to the danger and toxicity of this product before using it, we advise you to read its MSDS

Expiry date: 1 year (Storage between 5-35 °C)

ADDITIVES

Action	ADD	Dosage %	grams per 20 L can
Retarded Drying	980903 Retardant Additive	5% Maximum	
Antifoaming	980909 Antifoaming Addtive	0.5 - 1	

Note: the aforementioned data and the advices we give verbally, in writing or through tests, have been carried out following our loyal knowledge and mind, nevertheless they are considered as mere advices and indications without any obligation, and also with regard to the possible third party industrial property rights. Our advice does not exempt you from doing tests to the indications we may give you or to the products we may provide you, in order to check if these products are the suitable for the purposes indicated. The application, use and transformation of our products and of the products you manufacture under our technical advice will be made out of our vigilance and therefore will be of your sole responsibility. The sale of our products is under our Selling and Delivery General Conditions. If